



CERTIFIED CE SPRINKLER UNDER MOBIAK BRANDNAME

CODE 0135173

MBK15 - ACE12 - A0M

12Kg

A B C 40

Automatic Ceiling Fire Extinguisher **12Kg**.
Height **37cm**. Diameter **30,2cm!**

CE ASSEMBLY



**BIG DIAMETER
(160mm) CONICAL HOOP**

In Closed Rooms The Quantity Of The Extinguishing Agent Needed Is 12kg For An Area Of About 10m² And Height Of 1,5-2m From The Extinguishing Point. In Open Areas The Demanded Quantity Of The Extinguishing Agent Must Be Increased Due To Losses.



METALLIC pressure gauge with testing hole



CEILING BRACKET with bolt and nut for quick and easy installation



68°C SPRINKLER CE certified with SAFETY VALVE and built-in Charging Valve and thread for fixing Pressure Gauge



CONICAL HOOP with aligned holes for better and overall discharge, direct control of the pressure gauge as well as easy refilling of the fire extinguisher



Recommended Pressure Switch (10Bars) is connected to the Sprinkler of the extinguisher

FIRE EXTINGUISHERS CEILING DRY POWDER

The Unique Ceiling Fire extinguishers in the Market with PT 26bar and Thickness 2.5mm Providing Strongest Security

CODE 0135198

MBK15 - ACE12 - AOM - 122

12Kg

B C
20%

B C

Automatic Ceiling Fire Extinguisher **12Kg**.
Height **37cm**. Diameter **30,2cm!**

CE ASSEMBLY



CODE 0124046

MBK07 - MBK - CPCEILING

Automatic Ceiling Fire Extinguishers Fill - in Coupling



CODE 0141130

MBK14 - CEILING - PRESS

Pressure Switch for Ceiling Fire Extinguishers



CODE 0114052

KX11 - ACE - ADB

Adjustable Length Bracket suitable for multi height installation of Automatic Ceiling Fire Extinguishers. Mounting of the Automatic Ceiling Fire Extinguisher with bolt and nut. Length from 80 until 150cm.