

# FOAM TROLLEY FIRE EXTINGUISHERS WITH SEPARATE CARRIAGE MOUNTED ON THE VESSEL

Soft Material is Used in the Retaining wreaths of the Vessel to Avoid Injuries and Oxidation

3rd Wheel has been Added on the Front Side of the Fire Extinguisher Carriage for Easier Usage - Handling.



CODE 0135085

**MBK03 - 250AF - W1A**

25L<sup>t</sup> | FOAM | A IIB

25L<sup>t</sup> Trolley Fire Extinguisher with 5m Discharge Hose. **Pressure Gauge Safety Release Valve.**



**VESSEL WITH INTERNAL PLASTIC COATING**



**VESSEL WITH INTERNAL PLASTIC COATING**



CODE 0135033

**MBK03 - 500AF - W1B**

50L<sup>t</sup> | FOAM | A IIB

50L<sup>t</sup> Trolley Fire Extinguisher with 5m Discharge Hose. **Pressure Gauge Safety Release Valve.**



**VESSEL WITH INTERNAL PLASTIC COATING**



CODE 0135494



**MBK18 - 500AF - W1B**

50L<sup>t</sup> | FOAM | A IIB

50L<sup>t</sup> Trolley Fire Extinguisher with 5m Discharge Hose. **Pressure Gauge Safety Release Valve.**



VESSEL of 50mm Male Neck Thread	SEPARATE CARRIAGE mounted on the Vessel	Heavy Duty WHEELS
 <p>Double Edge Stainless steel valve SAFETY PIN</p>	 <p>Discharge Hose with gun type controlled discharge nozzle, made from advanced property material, bearing stainless steel springs for preventing permanent deformations of the discharge hose</p>	