

CERTIFIED CE SPRINKLER UNDER MOBIAK BRANDNAME



CODE 0135163

MBK15 - ACE1 - A0

1Kg | A B C 40

Automatic Ceiling Fire Extinguisher **1Kg** with Sprinkler Protective Cage (not included).
Height 25cm
Diameter 16cm

CE SPRINKLER

Cylinder Manufactured and Tested According to PED



CODE 0135121

MBK15 - ACE6 - A0R

6Kg | A B C 40

Automatic Ceiling Fire Extinguisher **6Kg**.
Height 40,5cm
Diameter 21,3cm

CE ASSEMBLY

BIG DIAMETER (160mm) CONICAL HOOP



METALLIC pressure gauge with testing hole



CEILING BRACKET with bolt and nut for quick and easy installation



68°C SPRINKLER CE certified with SAFETY VALVE and built-in Charging Valve and thread for fixing Pressure Gauge



CONICAL HOOP with aligned holes for better and overall discharge, direct control of the pressure gauge as well as easy refilling of the fire extinguisher



CODE 0135164

MBK15 - ACE3 - A0

3Kg | A B C 40

Automatic Ceiling Fire Extinguisher **3Kg**
Height 27,6cm
Diameter 24cm

CE ASSEMBLY



CODE 0124046

MBK07 - MBK - CPCEILING

Automatic Ceiling Fire Extinguishers Fill - in Coupling



CODE 0141130

MBK14 - CEILING - PRESS

Pressure Switch for Ceiling Fire Extinguishers



CODE 0114052

KX11 - ACE - ADB

Adjustable Length Bracket suitable for multi height installation of Automatic Ceiling Fire Extinguishers. Mounting of the Automatic Ceiling Fire Extinguisher with bolt and nut. Length from 80 until 150cm.



Recommended Pressure Switch (10Bars) is connected to the Sprinkler of the extinguisher

FIRE EXTINGUISHERS CEILING DRY POWDER

The Unique Ceiling Fire extinguishers in the Market with PT 26bar and Thickness 2.5mm Providing Strongest Security